

SHEETFED KALEIDO® INK

Product Overview

SHEETFED KALEIDO® INK provides superior performance for most sheetfed applications.

Features

- * Expands CMYK gamut to nearly RGB color range
- * Delivers superior performance for most sheetfed applications
- * Stable on-press performance
- * Similar results to 6- or 7- color printing via 4-color-process
- * Increased customer satisfaction
- * Fast make readies and reduced materials waste

Manufacturing Specifications

	<i>Yellow</i>	<i>Magenta</i>	<i>Cyan</i>	<i>Black</i>
Tack*1	13 +/- 5	14 +/- 5	15.5 +/- 5	14.5 +/- 5
Viscosity*2	500 +/- 50	600 +/- 50	700 +/- 50	300 +/- 50
V.O.C.(lbs./gal.)*3	1.91	0.73	0.79	0.94

*1 Ink-O-Meter @800rpm, 90°F

*2 Viscosity: Haake RT20 @77F (in Poise)

*3 Test Method: EPA 24

Actual tack on the press varies due to ink film thickness, image area, press speed, fountain solution, and the condition of the press and press room.

Shelf life: Approximately 1 year

Caution: We do not guarantee the Burn-out with coating. We strongly recommend doing a pre-test with actual paper and coating.

Packaging

Cans: kilo

All trademarks identified by the ® or ™ are registered trademarks or trademarks, respectively, of artience Co., Ltd or its subsidiary Toyo Ink America, LLC.

Toyo Ink America, LLC. (TIA), an artience group member company, makes no claims or warranty regarding information contained within this document and disclaims all liability relating in any way to this information. All printing applications should be fully evaluated prior to press production. TIA recommends consultation with its technical experts and trials before general use of any product. For more information, please consult your account manager. For technical questions, please contact your local TIA lab manager or field service technician.