

UV PST™ PROCESS SERIES TM LT

Product Overview

UV PST™ Process Series TM LT offers excellent printing properties similar to general purpose process inks. Manufactured for use on plastic substrates, but also suitable for a wide range of substrates.

Always check for adhesion before for live job.

Available Colors – Warm Red, Rhodamine Red, Purple, Violet, Green, Reflex Blue, Black Tint Base, Opaque White

Features

- * Good Adhesion on Plastics
- * Good cure speed
- * High-speed compatibility
- * Stable press performance

Manufacturing Specifications

SPECS	Yellow	Magenta	Cyan	Black
Tack*1	16.0+/-0.50	16.0+/-0.50	16.5+/-0.50	16.5+/-1.0
Viscosity*2	350+/-100	500+/-100	400+/-100	400+/-100
Flow*3	19+/-1.0	19+/-1.0	18+/-1.0	18+/-1.0

*1 Ink-O-Meter @800rpm, 90°F

*2 Viscosity: Haake RT20 @77F (in Poise)

*3 Spread-O-Meter Radius(mm) @77°F

Actual tack on the press varies due to ink film thickness, image area, press speed, fountain solution, and the condition of the press and press room.

Shelf life: Approximately 6 months

Packaging

Cans: 5 lbs.

All trademarks identified by the ® or ™ are registered trademarks or trademarks, respectively, of artience Co., Ltd or its subsidiary Toyo Ink America, LLC.

Toyo Ink America, LLC. (TIA), an artience group member company, makes no claims or warranty regarding information contained within this document and disclaims all liability relating in any way to this information. All printing applications should be fully evaluated prior to press production. TIA recommends consultation with its technical experts and trials before general use of any product. For more information, please consult your account manager. For technical questions, please contact your local TIA lab manager or field service technician.